

5035SD

, , 3/4" . (5035SD),



SD ()

20

SD

2.5L

5035 SD

SD

5035 SD

SD

(/), (CU)

(/), (CU)

	(mm)	(bar)	Q (m³/h)	D (m)	()					
					12x15	12x18	15x15	15x18	18x18	20x20
3.5x2.5L	3.0	1.240	27.2	6.9	5.7	5.5	4.6	3.8	3.1	
	4.0	1.430	27.2	7.9	6.6	6.4	5.3	4.4	3.6	
	5.0	1.620	27.2	9.0	7.5	7.2	6.0	5.0	4.1	
4.0x2.5L	3.0	1.490	28.0	8.3	6.9	6.6	5.5	4.6	3.7	
	4.0	1.740	29.0	9.7	8.1	7.7	6.4	5.4	4.4	
	5.0	1.950	29.2	10.8	9.0	8.7	7.2	6.0	4.9	
4.5x2.5L	3.0	1.790	29.7	9.9	8.3	8.0	6.6	5.5	4.5	
	4.0	2.070	30.2	11.5	9.6	9.2	7.7	6.4	5.2	
	5.0	2.320	32.2	12.9	10.7	10.3	8.6	7.2	5.8	
5.0x2.5L	3.0	2.110	31.5	11.7	9.8	9.4	7.8	6.5	5.3	
	4.0	2.400	33.2	13.3	11.1	10.7	8.9	7.4	6.0	
	5.0	2.690	35.2	14.9	12.5	12.0	10.0	8.3	6.7	
5.5x2.5L	3.0	2.390	32.2	13.3	11.1	10.6	8.9	7.4	6.0	
	4.0	2.760	34.2	15.3	12.8	12.3	10.2	8.5	6.9	
	5.0	3.090	35.0	17.2	14.3	13.7	11.4	9.5	7.7	
6.0x2.5L	3.0	2.700	34.2	15.0	12.5	12.0	10.0	8.3	6.8	
	4.0	3.160	36.0	17.6	14.6	14.0	11.7	9.8	7.9	
	5.0	3.540	34.0	19.7	16.4	15.7	13.1	10.9	8.9	
				CU < 85%	CU 85-88%	CU 88-92%	CU > 92%			

Sleeve Color	(mm)	P (bar)	Q (m³/h)	D ()	()					
					12x15	12x18	15x15	15x18	18x18	20x20
	3.5	2.5	0.720	24.0	4.0	3.3	3.2			
		3.0	0.790	24.0	4.4	3.7	3.5			
		4.0	0.910	25.0	5.1	4.2	4.0	3.4		
		5.0	1.040	25.0	5.8	4.8	4.6	3.9		
		2.5	0.950	26.0	5.3	4.4	4.2	3.5		
4.0	3.0	1.040	26.0	5.8	4.8	4.6	3.9			
	4.0	1.200	26.0	6.7	5.6	5.3	4.4	3.7		
	5.0	1.350	28.0	7.5	6.3	6.0	5.0	4.2		
4.5	2.5	1.210	28.0	6.7	5.6	5.4	4.5			
	3.0	1.320	28.0	7.3	6.1	5.9	4.9	4.1		
	4.0	1.540	29.0	14.1	11.8	11.3	9.4	7.8		
	5.0	1.710	30.0	9.5	7.9	7.6	6.3	5.3		
	2.5	1.460	29.0	8.1	6.8	6.5	5.4	4.5		
5.0	3.0	1.610	29.0	8.9	7.5	7.2	6.0	5.0	4.0	
	4.0	1.870	31.0	10.4	8.7	8.3	6.9	5.8	4.7	
	5.0	2.100	32.0	11.7	9.7	9.3	7.8	6.5	5.3	
	2.5	1.760	30.0	9.8	8.1	7.8	6.5	5.4	4.4	
5.5	3.0	1.930	31.0	10.7	8.9	8.6	7.1	6.0	4.8	
	4.0	2.230	34.0	12.4	10.3	9.9	8.3	6.9	5.6	
	5.0	2.490	35.0	13.8	11.5	11.1	9.2	7.7	6.2	
6.0	2.5	2.060	30.0	11.4	9.5	9.2	7.6	6.4	5.2	
	3.0	2.260	32.0	12.6	10.5	10.0	8.4	7.0	5.7	
	4.0	2.620	34.0	14.6	12.1	11.6	9.7	8.1	6.6	
	5.0	2.940	36.0	16.3	13.6	13.1	10.9	9.1	7.4	
				CU < 85%	CU 85-88%	CU 88-92%	CU > 92%			

: 2.5L -

PROF Irrigation

Москва, ул. Молодогвардейская, д.54.

Тел.: 8(495)790-2951

Сайт: profirrigation.ru

E-mail: profirrig@mail.ru

5035SD-PC

, 3/4" .

:

-
-
-
-
-

18



- 5035 PC SD

(mm)	P (bar)	Q (m ³ /h)	D (m)
3.5*	2.5	0.720	26
	3.0	0.790	27
	4.0	0.910	27
	5.0	1.020	28
4.0	2.5	0.950	27
	3.0	1.040	28
	4.0	1.200	28
	5.0	1.350	29
4.5	2.5	1.210	28
	3.0	1.320	30
	4.0	1.540	31
	5.0	1.710	32
5.0	2.5	1.460	30
	3.0	1.610	31
	4.0	1.870	33
	5.0	2.100	34

*
*

PROF Irrigation

Москва, ул. Молодогвардейская, д.54.
Тел.: 8(495)790-2951
Сайт: profirrigation.ru
E-mail: profirrig@mail.ru